

The RHINO Goods lift At-a-glance...

Installation is Quick and Straightforward

The Rhino is simply a 'Beast'. It keeps going and going, day-in, day-out, and it's ability to take a battering is unbelievable. And yet, it's also one of the easiest and quickest goods lifts to install and maintain... there little or no pit, which means you don't have all the hassle of putting in new foundations for all the machinery; and the lift framework can be sited pretty much anywhere there's the space. The Rhino Pro is also capable of transporting trained users and wheelchairs.

0800 085 3211

contact@pickeringslifts.co.uk

www.pickeringslifts.co.uk



Gate options

- 1 Manual swing landing doors (standard)
- 2 Galvanised manual shutter landing gate
- 3 Galvanised car picket gate



Drive unit type

Geared traction machine, VVVF speed regulator, chain drive



Lift car dimensions

Width: from 1000mm to 2000mm in 100mm increments

Depth: from 1000mm to 2000mm in 100mm increments

Internal height: 1800, 1900, 2000 (standard), 2100, 2200mm



Power supply

3-phase 415 Vac



Travel

Maximum of 9m



Rated speed

0.15m/s



Rated load

500, 1000, 1500 or 2000kg



Landing doors

Manual swing with vision panel finished in epoxy painted steel, RAL 9005 black.

Entrance configuration

Front and through option



Lift car build

Rhino (Goods only)

- Car and floor finished in RAL 7032 beige
- Tube lighting
- Other finishes available on request

Rhino Pro (Goods and personal)

- Galvanised car ceiling
- Handrail
- Floor push buttons
- Attendant key switch
- Alarm button
- Stop switch
- EN81-70 features



Control system

Rhino:

- APB call and send lift control system from landings
- One emergency brake

Rhino Pro:

- APB call and send on landings and constant pressure lift control in car
- Two emergency brakes
- Unintended car movement (UCM) system



Number of levels

Maximum of 4 levels



Height of structure

Maximum 12m



100mm Pit

Virtually no pit needed. If 100mm pit is not available, then 100mm primed steel external ramps can be provided to allow full access



Shaft lighting

Direct fluorescent light



Minimum dimensions

Lift car width + 470mm
Lift car depth + 180mm
Headroom car height + 700mm

Just a few of the Rhino Optional Extras

- Access ramps
- Landing door options
- Manual picket gates, Bump rails and button style options
- Car floor options
- Auto dialler
- Out-of-service key switch
- Machinery access ladder

UK-wide

- 13 Regional Offices
- Largest Independent Lift Installer and Maintenance Provider in the UK
- Family owned and run



Search for
Pickerings Lifts
on Social Media

0800 085 3211

contact@pickeringslifts.co.uk

Passenger Lifts | Goods Lifts | Service Lifts | Platform Lifts

#YourTrustedPartner #RealPeople

Copyright Pickerings Lifts 2021

24
hours

days
a week 7

365
days a year



PICKERINGS LIFTS