



GoEasy

Datasheet/Lift Finishes

8 Person Traction Machine Roomless Lift

2 to 6 Stops

Open to the front only | Open Protocol Solution



PICKERINGS LIFTS

Pickerings Lifts

GoEasy | Datasheet

KEY DIMENSIONS TO BE CONFIRMED BY CLIENT

Dimension	Range (mm)	Constructed Dimension
Shaft Width	1650-1800	
Shaft Depth	1750-1900	
Pit Depth	1050-1500	
Travel 0-1	2500-5000	
Travel 1-2	2500-5000	
Travel 2-3	2500-5000	
Travel 3-4	2500-5000	
Travel 4-5	2500-5000	
Headroom	3600min	

SPECIFICATION

Walls:	K01 - White as standard (See wall finishes)
Mirrors:	Half height - to rear wall
Handrail:	P13 - Brushed stainless steel
Ceiling:	L40 - Platinum finish
Floor:	R59 - Vinyl stone grey concrete
Operating panel:	X02 - Brushed stainless steel
Operating panel frame:	AL04 - Black
Display:	LCD
Landing entrances:	Brushed stainless steel
Car door:	Brushed stainless steel
Shaft fixings:	Masonry shaft only

ADDITIONAL FEATURES INCLUDED

Energy saving auto shut down

Shaft lighting

Drill fixings

CAR OPERATING PANEL




PUSH BUTTONS BRAILLE OVER INJECTED



FLOOR FINISH

Stone rubber



R59 Vinyl Stone
Grey Concrete

WALL FINISHES

Options available below



K01
White




K04
Night Black



K10
Atlantic Blue



K11
Techno Grey



K17
Nature Beige



PICKERINGS LIFTS